


RUBBER SPHERICAL WHEELS



Description

Black rubber spherical wheels with chrome-plated brackets and electrolytically galvanised Zamak alloy fittings. The wheels are supplied in pair only (one right and one left wheels).

Uses

Suitable for indoor applications, without aggressive chemicals. They can be used on fragile floors, even carpet. Examples of recommended applications: house and office furniture with low carrying capacity.

Environments of use

Suitable for domestic environments without aggressive chemicals.

WEAK ACIDS		WEAK BASES	
STRONG ACIDS		STRONG BASES	
WATER		HYDROCARBONS	
ALCOHOL		SOLVENTS	

For information on the compatibility of the component wheel materials with specific aggressive chemical substances, see table at page 36.

Floors

Suitable on tiles and delicate flooring; not recommended on abrasive, unpaved floors or in presence of processing residues. Not recommended in presence of obstacles.





mm	RH		LH		mm	mm	mm	mm	daN
	kg	CODE	kg	CODE					
45	0.09	354101	0.09	354201	56	28x28	19x19	5	20
55	0.14	354102	0.14	354202	66	38x38	27x27	5	30
65	0.19	354103	0.19	354203	76	38x38	27x27	5	40



mm	RH		LH		mm	mm	mm	mm	daN
	kg	CODE	kg	CODE					
45	0.09	356101	0.09	356201	52	SPANNER 12	M8	15	20
55	0.13	356102	0.13	356202	62	SPANNER 12	M8	15	30
65	0.18	356103	0.18	356203	72	SPANNER 12	M10	15	40



Package with 2 wheels and 4 fittings

mm	kg	CODE	mm	mm	mm	mm	mm	mm	mm	daN
55	0.35	350002	62	38x38	27x27	5	SPANNER 12	M8	15	30