

## Long-Length PowerGrip® HTD® Belting

PowerGrip HTD belts have a larger, more robust tooth profile for increased capacity, as compared to timing belts.

### Markets/Applications

Long length PowerGrip HTD belting is a cost effective, low maintenance drive alternative that is well suited for linear movement, positing and conveying applications.

### Features/Advantages

- **Fiberglass tensile cord** provides high strength, excellent flex life, and high resistance to elongation. Steel tensile cord is available in some belt types for added length stability.
- **Neoprene body** provides protection against grime, grease, oil, and moisture.
- **Nylon tooth facing** provides a durable wear surface for long service life.
- Eliminates lubrication and re-tensioning to reduce maintenance and labor required on drives.



### Recommended Sprockets

PowerGrip HTD Sprockets

### Notes

Minimum order lengths for fiberglass tensile cord belting is 50 feet, ordered in 50 foot increments thereafter.

Minimum order lengths for steel tensile belting is 98 feet, ordered in 98 foot increments thereafter.

Continuous lengths, if needed, must be specified when ordering, and must be ordered in increments of the minimum order quantity (unless ordering the maximum continuous lengths).

Continuous lengths may require lead times.

Minimum order quantities may vary for non-standard widths. Check with Customer Service.

### Product No. Series 9308

#### 3mm Pitch

Part No.	Product No.	Width (mm)	Net Wt. per Ft.	Min Order Qty	Max. Cont. Length
LL3M06	9308-0044	6	.01	50 ft.	300 ft.
LL3M09	9308-0003	9	.01	50 ft.	300 ft.
LL3M15	9308-0084	15	.01	50 ft.	185 ft.

#### 5mm Pitch

Part No.	Product No.	Width (mm)	Net Wt. per Ft.	Min Order Qty	Max. Cont. Length
LL5M09	9308-0045	9	.01	50 ft.	300 ft.
LL5M15	9308-0033	15	.04	50 ft.	185 ft.
LL5M25	9308-0025	25	.05	50 ft.	100 ft.

#### 8mm Pitch

Part No.	Product No.	Width (mm)	Net Wt. per Ft.	Min Order Qty	Max. Cont. Length
<sup>17</sup> LL8M20	9308-0001	20	.08	50 ft.	170 ft.
<sup>17</sup> LL8M30	9308-0004	30	.13	50 ft.	300 ft.
<sup>17</sup> LL8M50	9308-0005	50	.21	50 ft.	300 ft.
<sup>17</sup> LL8M85	9308-0006	85	.36	50 ft.	300 ft.

#### 14mm Pitch

Part No.	Product No.	Width (mm)	Net Wt. per Ft.	Min Order Qty	Max. Cont. Length
LL14M40	9308-10009	40	.26	98 ft.	392 ft.
LL14M55	9308-10020	55	.35	98 ft.	392 ft.
LL14M85	9308-10057	85	.55	98 ft.	392 ft.

#### Steel Tensile — 14mm Pitch

Part No.	Product No.	Width (mm)	Net Wt. per Ft.	Min Order Qty	Max. Cont. Length
LL14M40 ST	9308-10016	40	.76	98 ft.	392 ft.
LL14M55 ST	9308-10051	55	1.02	98 ft.	392 ft.
LL14M85 ST	9308-10084	85	1.51	98 ft.	392 ft.

LONG-LENGTH BELTING

<sup>17</sup> Longer continuous lengths may be available by special order, contact Customer Service.

