

Highly flexible PVC hose, light

## Applications

- flexible hose/ ducting for gases and for dust, powder, fibres
- industrial vacuum cleaners, vacuum cleaners
- construction drying
- medical device/ medical technology, health-care sector: cable protection conduit, air supply hose, extraction hose
- scrubber, floor cleaning machine

## Properties

- light weight
- highly flexible
- good resistance to alkalis and acids
- good resistance to chemicals
- conforms to RoHS guideline

## Temperature Range

- 0°C to 85°C

## Design, Material

SuperFlex design

- plastic coated spring steel wire
- wall: high grade soft PVC

## Delivery variants

- further diameters and lengths available on request
- black (standard)


I.D. in / mm	O.D. mm	Over- pressure bar	Under- pressure bar	Bending Radius mm	Weight kg/m	Dimensions in Stock m	Order No.
<b>standard version, reinforced, left-hand pitch</b>							
1 / 25	31	1,700	0,200	13	0,200	15	372-0025-0000
- / 28	34	1,600	0,200	14	0,230	15	372-0028-0000
1,25 / 32	38	1,500	0,200	16	0,280	15	372-0032-0000
1,36 / 35	41	1,400	0,200	18	0,310	15	372-0035-0000
1,5 / 38	44	1,400	0,200	19	0,340	15	372-0038-0000
- / 41	47	1,400	0,180	21	0,370	15	372-0041-0000
1,75 / 44-45	50	1,300	0,160	22	0,380	15	372-0044-0000
2 / 50-51	57	1,300	0,150	26	0,460	15	372-0051-0000
2,5 / 63-65	69	1,000	0,140	31	0,530	15	372-0063-0000
- / 70	76	0,900	0,120	35	0,580	15	372-0070-0000
3 / 75-76	82	0,800	0,100	38	0,680	15	372-0076-0000
- / 80	86	0,700	0,090	40	0,830	15	372-0080-0000
3,5 / 89-90	95	0,700	0,090	45	0,930	15	372-0089-0000
4 / 100-102	106	0,600	0,080	52	1,000	15	372-0100-0000
<b>flexible type, less bending force, flexible at low temp. (down to -25°C), without reinforcement, right-hand pitch</b>							
1 / 25	31	1,100	0,250	13	0,234	15	372-0025-0001
- / 28	34	0,950	0,240	14	0,257	15	372-0028-0001
1,25 / 32	38	0,875	0,230	16	0,290	15	372-0032-0001
1,36 / 35	41	0,800	0,225	18	0,315	15	372-0035-0001
1,5 / 38	44	0,740	0,215	19	0,339	15	372-0038-0001
- / 41	47	0,705	0,210	21	0,364	15	372-0041-0001
1,75 / 44-45	50	0,630	0,195	22	0,388	15	372-0044-0001
2 / 50-51	57	0,565	0,180	26	0,437	15	372-0051-0001
2,5 / 63-65	69	0,440	0,125	31	0,544	15	372-0063-0001
- / 70	76	0,410	0,105	35	0,607	15	372-0070-0001
3 / 75-76	82	0,380	0,095	38	0,653	15	372-0076-0001
- / 80	86	0,360	0,090	40	0,690	15	372-0080-0001
3,5 / 89-90	95	0,320	0,075	45	0,764	15	372-0089-0001
4 / 100-102	106	0,285	0,060	52	0,867	15	372-0100-0001

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional technical data at [www.norres.com/en/technology/](http://www.norres.com/en/technology/)

## Accessories



CLAMP 208



CONNECT 228



CONNECT 223



CONNECT 226



CONNECT 270-271

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. Additional technical data at [www.norres.com](http://www.norres.com). The right to make technical modifications is reserved. All values determined at 20°C and are approx. data.