



Oil Suction & Deliver hose

Temperature range

-15° C - +60° C

Features

Plasticized PVC hose with incorporated reinforcement of anti-shock rigid PVC spiral. Inside surface smooth, light corrugation outside. Very strong and resistant to crushing, abrasion, atmospherical agents and most chemicals.

Product is available per order.

Applications

Suction and delivery of carburants, petrol, gas, mineral oil, etc.

Internal diameter [mm]	Weight [g/m]	Wall thickness [mm]	Bend radius [mm]	Working pressure [bar]	Max. pressure [bar]	Vacuum [m/H2O]	Package [m]	Package Size [m3]
20	420	4,0	140	8	24	10	30	0,054
25	550	4,3	168	8	24	10	30	0,059
30	650	4,5	195	8	24	10	30	0,087
32	700	4,5	205	8	24	10	30	0,096
35	750	4,5	220	7	21	10	30	0,119
38	780	4,8	235	7	21	10	30	0,125
40	800	5,0	255	7	21	10	30	0,130
45	950	5,0	275	6	18	10	30	0,175
50	1150	5,0	300	6	18	10	30	0,209
55	1400	5,5	330	6	18	10	30	0,235
60	1150	5,6	355	6	18	10	30	0,304
63	1680	5,6	370	6	18	10	30	0,317
70	1900	5,8	410	5	15	10	30	0,359
76	2000	5,8	440	5	15	10	30	0,436
80	2200	6,0	460	5	15	10	30	0,589
90	2600	7,0	530	4	12	10	30	0,622
100	3330	7,5	600	4	12	9	30	0,936
110	3650	7,5	690	4	12	9	30	1,000