

ABRAPLUS /40

PLASTER HOSE



APPLICATION

Plaster hoses

TUBE

Black, smooth, **NR/SBR** antistatic rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, antistatic cloth impression **NR/SBR** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-40°F + 158°F

SPECIFICATIONS

DIN 53516 70 ± 5mm³

| ID | | OD | | WEIGHT | WP | | BP | | COIL LENGTH |
|-----|---------|-----|---------|--------|-----|-----|-----|------|-------------|
| mm | inch | mm | inch | kg/m | bar | psi | bar | psi | m |
| 25 | 1 | 37 | 1 15/32 | 0,73 | 40 | 600 | 120 | 1800 | 40/61 |
| 25 | 1 | 38 | 1 1/2 | 0,80 | 40 | 600 | 120 | 1800 | 40/61 |
| 32 | 1 1/4 | 46 | 1 13/16 | 1,07 | 40 | 600 | 120 | 1800 | 40/61 |
| 35 | 1 3/8 | 49 | 1 15/16 | 1,23 | 40 | 600 | 120 | 1800 | 40/61 |
| 38 | 1 1/2 | 54 | 2 1/8 | 1,44 | 40 | 600 | 120 | 1800 | 40/61 |
| 40 | 1 9/16 | 56 | 2 5/32 | 1,52 | 40 | 600 | 120 | 1800 | 40/61 |
| 51 | 2 | 68 | 2 11/16 | 1,99 | 40 | 600 | 120 | 1800 | 40/61 |
| 65 | 2 9/16 | 85 | 3 11/32 | 2,90 | 40 | 600 | 120 | 1800 | 40/61 |
| 76 | 3 | 95 | 3 3/4 | 3,19 | 40 | 600 | 120 | 1800 | 40/61 |
| 80 | 3 5/32 | 100 | 3 15/16 | 3,53 | 40 | 600 | 120 | 1800 | 40/61 |
| 90 | 3 35/64 | 110 | 4 21/64 | 3,93 | 40 | 600 | 120 | 1800 | 40/61 |
| 102 | 4 | 122 | 4 13/16 | 4,50 | 40 | 600 | 120 | 1800 | 40/61 |

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

